

low level

opacity and dust

compliance monitoring



LAND

Combustion & Environmental Monitoring

An **AMETEK**® Company

4500 Premier

High accuracy monitoring for low level dust and opacity


Land is a world leader in dust monitor design and manufacture, with a commitment to continuous product improvement.

The Model 4500 Premier meets the latest and most demanding standards for low level dust monitoring.



Worldwide approvals for compliance monitoring

- Meets or exceeds US EPA requirements for 40CFR60 Sections 13, 17 and App. B PS1
- Meets or exceeds US EPA requirements for proposed 40CFR60 App. F Procedure 3
- Meets or exceeds ASTM Standard D6216
- Meets or exceeds US EPA CPS-001 for 0 to 10 % Opacity monitors
- MCerts certified Continuous Emissions Monitoring System
- TÜV approved to the requirements of the 13th, 17th, 27th & 30th BImSchV and TA Luft 2002



Features and Benefits

- Ultra-low level measurement - *advanced LED design gives 0 to 10 mg/m³ dust density capability*
- Outstanding reliability, low maintenance - *Measures with no moving parts*
- High accuracy and repeatability - *Designed for compliance monitoring applications*
- Patented measurement technology - *Unique “no drift” zero check*
- Automatic in-situ zero and span checking - *Built-in calibration audit jig*
- Range of instrument configurations - *Outputs in opacity, extinction, or dust density*
- Fully user configurable - *Integral control panel for set-up, control and diagnostics*
- Easily integrated into plant control system - *Current loop outputs and Modbus interface*

Patented Technology

The Model 4500 Premier uses a highly homogeneous advanced LED light source⁺ to reduce the effect of misalignment on the measured opacity. Together with the patented* “Flood LED”, it achieves the highest levels of stability and accuracy. The “no moving parts” optical system gives an instrument with exceptional reliability.

⁺US Patent No. 6781695

^{*}UK Patent No. 2287785



Easy Auditing

Periodic performance verification could not be simpler. The built-in audit jig accepts standard optical filters, and the zero alignment can be confirmed without removing the instrument from the stack.



Dust Density

Dust density monitors must be calibrated by comparison with an isokinetic sample test, as proposed in PS-11. The Model 4500 Premier fully supports this operation with automatic averaging and calculation.

Quick Installation

The stainless steel Termination Box has a single, pre-terminated cable for connection to the instrument itself. All customer connections are made using simple terminal rails inside the box.

Automatic Calibration

The Model 4500 Premier is fitted with a fully automatic zero checking and drift compensation system. An automatic span check mechanism confirms the instrument calibration at user defined intervals.

Simple Setup

The integral control panel provides all user setup and control. Detailed diagnostic information can be accessed through the key panel.

Applications include:

- Incineration
- Power utilities
- Pulp and paper
- Cement and roadstone
- Steel (Electric Arc Furnace)
- Glass
- Refineries
- Petrochemicals
- Process Industries

Further Information

UK

Land Instruments International Ltd
Dronfield,
Derbyshire, S18 1DJ
Tel: +44 (0) 1246 417691
Fax: +44 (0) 1246 290274
E-Mail: combustion.info@landinst.com
Web: www.landinst.com

USA

Ametek LAND, Inc.
10 Friends Lane
Newtown, PA 18940-1804
Tel: +1 215 504 8000
Fax: +1 215 504 0879
E-Mail: combsales@landinstruments.net
Web: www.landinstruments.net

Poland

Land Instruments Sp z o.o.
ul. Michalowskiego 5/2
31 - 126 Krakow
Tel: +48 (0) 12 632 82 62
Fax: +48 (0) 12 632 24 74
E-Mail: land@land.com.pl
Web: www.land.com.pl

Italy

Land Instruments SRL
Via dell'Industria, 2
20037 Paderno Dugnano MI
Tel: +39 02 9904 0423, 9108 0020
Fax: +39 02 99 04 0418
E-Mail: comb.info@landinst.it
Web: www.landinst.it

France

Land Instruments Sarl
7 Parc des Fontenelles
78870 Bailly
Tel: +33 (0) 1 30 80 89 20
Fax: +33 (0) 1 30 80 89 21
E-Mail: info-combustion@landinst.fr
Web: www.landinst.fr

Mexico

Land Instruments International
Av. Horacia 1132 Planta Baja "B"
Col. Polanco
11550 MEXICO D.F.
Tel + 52 55 5281 1165
Fax + 52 55 5281 5364
E-Mail: ventas@landinstruments.net

Specifications

Measuring

Technique:	Double pass/path transmissometry
Operating Wavelength:	520 ± 20 nm, High Intensity LED
Range (User selectable):	Opacity 0 – 10 % to 0 – 100 %; Optical Density 0 – 0.1 to 0 – 3.0 Dust Density 0 - 10 to 0 - 4000 mg/m ³
Accuracy:	± 0.5 % opacity
Linearity:	< 2 % of range
Resolution:	0.1 % Opacity; 0.001 Optical Density; 0.1 mg/m ³ Dust
Drift:	< 1 % of range per month
Suitable for Stacks diameter:	0.6 to 9.7 m / 2 to 32 ft
Installation Pathlength:	0.97 to 10 m / 3 to 22 ft (option to 20 m / 66 ft)
Calibration:	Automatic zero and upscale calibration
Response Time:	< 10s (< 2s with no damping)
Calibration Error per ASTM D6216:	< 1 % opacity
24 Hour Drift:	< 0.3 % opacity
Long Term Drift:	< 0.3 % opacity per month
Voltage Variation per ASTM D6216:	< 0.2 % opacity (over 85 - 264 V a.c.)
Thermal Stability per ASTM D6216:	< 0.3 % opacity (over -20 to +55 °C / -4 to +131 °F range)
Ambient Light Sensitivity per ASTM D6216:	< 0.3 % opacity
Insensitivity to Misalignment:	< 0.2 % opacity for ±0.25 ° misalignment
Zero Correction:	Automatic correction for zero drift
Averaging:	Selectable from 10 secs to 24 hours (in 1 second steps)

Environmental

Operating Temperature:	-20 to 55 °C / -4 to 131 °F (-40 °C / -40 °F with optional heater)
Max. Flue Gas Temp.:	600 °C / 1112 °F
Max. Flange Temp.:	200 °C / 392 °F
Environmental Rating:	IP65 / NEMA4X

Compliance

Measurement Standards:	Meets or exceeds US EPA requirements for 40CFR60 Sections 13, 17 and App. B PS1 Meets or exceeds US EPA requirements for proposed 40CFR60 App. F Procedure 3 Meets or exceeds ASTM Standard D6216-03 Meets or exceeds US EPA CPS-001 MCerts certified Continuous Emissions Monitoring System TÜV approved to the requirements of the 13 th , 17 th , 27 th & 30 th BImSchV and TA Luft 2002
Safety:	Conforms to EN-61010-2
EMC:	Conforms to EN-50 081 & EN-50 082

Outputs

Modbus Interface:	RS232 or RS485
Analog Outputs:	Two isolated 4-20mA current outputs. Independently configurable as Opacity, Dust Optical Density, Calibration Drift or OPLR
Relay Outputs:	System OK, Span calibration, Zero calibration, Alarm 1, Alarm 2, Maintenance
Relay Rating:	1 A @ 24 V d.c., 1 A @ 240 V a.c.

Electrical

Power Supply:	100 – 240 V a.c.+10%, -15%, 50 – 60 Hz
Power Rating:	10 W

Mechanical Data

Dimensions (HxWxD)	
Transceiver	220 x 220 x 520 mm / 9 x 9 x 20.5 in
Retro-reflector	220 x 220 x 320 mm / 9 x 9 x 12.6 in
Termination box	180 x 400 x 120 mm / 7 x 16 x 5 in
Weight Transceiver	15.2 kg / 33.5 lb
Weight Retro-reflector	7.6 kg / 16.8 lb
Weight Termination Box	7.5 kg / 16.5 lb

Options

Air Blower Units	Control Room Unit
Automatic Fail-safe Shutters	Alignment Tool
Weather Covers	Calibration Filters

Continuous product development may make it necessary to change these details without notice

LAND

www.landinst.com

An **AMETEK** Company

LAND has a comprehensive range of Combustion and Environmental Monitoring Instrumentation.



Sira MC 040029/00

PDS 197/09/06